



DESIGN
DRIVEN
ACOUSTICS



Cleaning Instructions

RECOMMENDED CLEANING SOLUTIONS

- 50/50 solution of warm water and bleach (5.25% sodium hypochlorite solution)
- 3% Hydrogen peroxide
- Distilled water (for stain removal only)

RECOMMENDED CLEANING STEPS

1. Blot fresh spills as soon as possible to avoid the liquid absorbing into the product.
2. If the stain is dry and there is visible soil, use a plastic bristle brush to soften the dirt.
Avoid excess pressure.
3. Vacuum the surface thoroughly using a dusting brush attachment.
4. Apply appropriate cleaning solution (see recommended cleaning solutions above) to a piece of white and lint free cloth. Use a hand spray applicator, do not oversoak.
Avoid using bleach on printed products.
5. Using the treated cloth, blot the stain starting from the outer edge and moving inward.
6. If required, renew the cleaning cloth. Repeat process until there is no further transfer of the dirt to the cloth.
7. Once the stain is removed, soak up all remaining cleaning solution with a dry cloth.
8. Use a clean cloth or sponge soaked in water to remove any residue.
9. Allow treated surface to air dry.

MITIGATION OF MICROBIAL / VIRAL CONTAMINATION

Proper PPE must be worn ie. bleach odor respirator, protective eyewear and gloves.

1. Mix equal amount of water and bleach (5.25% sodium hypochlorite solution).
2. Use a hand spray applicator to mist the surface of product, apply generously.
3. Allow treated surface to air dry.