1512 S BATAVIA AVENUE GENEVA, IL 60134 630-232-0104

Test Report

www.riverbankacoustics.com

**Sound Absorption** 

FOUNDED 1918 BY WALLACE CLEMENT SABINE

SPONSOR: Archifibe Inc.

Mississauga, Ontario, Canada

RAL<sup>TM</sup>-A22-428 CONDUCTED: 2022-09-28 Page 1 of 9

ON: EzoLayer 50mm

#### TEST METHODOLOGY

Riverbank Acoustical Laboratories<sup>TM</sup> is accredited by the U.S. Department of Commerce, National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) as an ISO 17025:2017 Laboratory (NVLAP Lab Code: 100227-0) and for this test procedure. The test reported in this document conformed explicitly with ASTM C423-22: "Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method." The specimen mounting was performed according to ASTM E795-16: "Standard Practices for Mounting Test Specimens During Sound Absorption Tests." A description of the measurement procedure and room specifications are available upon request. The results presented in this report apply to the sample as received from the test sponsor.

#### <u>INFORMATION PROVIDED BY SPONSOR</u>

The test specimen was designated by the sponsor as EzoLayer 50mm. The following nominal product information was provided by the sponsor prior to testing. The accuracy of such sponsor-provided information can affect the validity of the test results.

#### **Product Under Test**

Product Name: EzoLayer 50mm Manufacturer: Archifibe Inc.

#### SPECIMEN MEASUREMENTS & TEST CONDITIONS

Through a full external visual inspection performed on the test specimen, Riverbank personnel verified the following information:

#### **Test Specimen**

Dimensions: 8 panels @ 610 mm (24 in.) by 1372 mm (54 in.)

Thickness: 50.93 mm (2.005 in.) Overall Weight: 31.64 kg (69.75 lbs) Mass per Unit Volume: 92.9 kg/m<sup>3</sup> (5.80 lbs/ft<sup>3</sup>)



® RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT. THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE

SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

1512 S BATAVIA AVENUE GENEVA, IL 60134 630-232-0104

Test Report

www.riverbankacoustics.com

FOUNDED 1918 BY WALLACE CLEMENT SABINE

Archifibe Inc. 2022-09-28

RALTM-A22-428 Page 2 of 9

**Overall Specimen Properties** 

Size: 2.44 m (96.0 in) wide by 2.74 m (108.0 in) long

Thickness: 0.05 m (2.004 in) Weight: 31.64 kg (69.75 lbs)

Mass per Unit Area: 4.73 kg/m<sup>2</sup> (0.97 lbs/ft<sup>2</sup>)

Calculation Area: 6.689 m<sup>2</sup> (72. ft<sup>2</sup>)

**Test Environment** 


Room Volume: 291.98 m<sup>3</sup>

Temperature:  $21.6 \,^{\circ}\text{C} \pm 0.2 \,^{\circ}\text{C}$  (Requirement:  $\geq 10 \,^{\circ}\text{C}$  and  $\leq 5 \,^{\circ}\text{C}$  change) Relative Humidity:  $57.2 \% \pm 1.4 \%$  (Requirement:  $\geq 40 \%$  and  $\leq 5 \%$  change)

Barometric Pressure: 100.2 kPa (Requirement not defined)

#### **MOUNTING METHOD**

Type A Mounting: The test specimen was laid directly against the test surface. Per sponsor request, the perimeter edges were left exposed.



1512 S BATAVIA AVENUE GENEVA, IL 60134 630-232-0104

Test Report

www.riverbankacoustics.com

FOUNDED 1918 BY WALLACE CLEMENT SABINE

**RALTM-A22-428** 

Page 3 of 9

Archifibe Inc. 2022-09-28



Figure 1 – Specimen mounted in test chamber





Figure 2 – Individual specimen panel



® RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT. THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE

SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

1512 S BATAVIA AVENUE GENEVA, IL 60134 630-232-0104 Test Report

www.riverbankacoustics.com

FOUNDED 1918 BY WALLACE CLEMENT SABINE

RAL<sup>TM</sup>-A22-428
Page 4 of 9

**Archifibe Inc.** 2022-09-28



Figure 3 – Detail of specimen materials



® RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT.

THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

1512 S BATAVIA AVENUE GENEVA, IL 60134 630-232-0104 Test Report

www.riverbankacoustics.com

FOUNDED 1918 BY WALLACE CLEMENT SABINE

RAL<sup>TM</sup>-A22-428
Page 5 of 9

**Archifibe Inc.** 2022-09-28

#### TEST RESULTS

Specimen total absorption and absorption coefficient are tabulated at the eighteen standard frequencies. A graphic presentation of the data and additional information appear on the following pages.

1/3 Octave Center				
Frequency	Total Absorption	Total Absorption	Absorption	
(Hz)	$(m^2)$	(Sabins)	Coefficient	
100	1.49	16.02	0.22	
** 125	2.36	25.43	0.35	
160	3.30	35.48	0.49	
200	4.35	46.87	0.65	
** 250	5.24	56.45	0.78	
315	6.64	71.51	0.99	
400	7.30	78.54	1.09	
** 500	8.15	87.71	1.22	
630	8.47	91.16	1.27	
800	8.42	90.60	1.26	
** 1000	8.52	91.76	1.27	
1250	8.48	91.32	1.27	
1600	8.28	89.13	1.24	
** 2000	8.14	87.58	1.22	
2500	7.68	82.63	1.15	
3150	7.45	80.23	1.11	
** 4000	7.66	82.48	1.15	
5000	7.76	83.55	1.16	

SAA = 1.12 NRC = 1.10



1512 S BATAVIA AVENUE GENEVA, IL 60134 630-232-0104 Test Report

www.riverbankacoustics.com

FOUNDED 1918 BY WALLACE CLEMENT SABINE

**Archifibe Inc.** 2022-09-28

RAL<sup>TM</sup>-A22-428
Page 6 of 9

### TEST RESULTS (continued)

The sound absorption average (SAA) is defined in ASTM C423-17 Section 3.1.1 as the arithmetic average of the sound absorption coefficients of a material for the twelve one-third octave bands from 200 Hz through 2500 Hz, inclusive, rounded to the nearest integer multiple of 0.01.

The noise reduction coefficient (NRC) is defined from previous versions of ASTM C423 as the arithmetic average of the sound absorption coefficients at 250 Hz, 500 Hz, 1000 Hz, and 2000 Hz, rounded to the nearest integer multiple of 0.05.

Tested by

Marc Sciaky

Senior Experimentalist

Report by

Keith Kimberling

Test Engineer

Approved by

Eric P. Wolfram

Laboratory Manager

SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

1512 S BATAVIA AVENUE GENEVA, IL 60134 630-232-0104

Test Report


www.riverbankacoustics.com

FOUNDED 1918 BY WALLACE CLEMENT SABINE

RALTM-A22-428 Page 7 of 9

Archifibe Inc. 2022-09-28

### SOUND ABSORPTION REPORT



SAA = 1.12NRC = 1.10



® RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NYLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT.

THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

1512 S BATAVIA AVENUE GENEVA, IL 60134 630-232-0104 Test Report

www.riverbankacoustics.com

FOUNDED 1918 BY WALLACE CLEMENT SABINE

**Archifibe Inc.** 2022-09-28

Page 8 of 9

#### **APPENDIX A: Extended Frequency Range Data**

Specimen: EzoLayer 50mm (See Full Report)

The following non-accredited data were obtained in accordance with ASTM C423-22, but extend beyond the defined frequency range of 100Hz to 5,000Hz. These unofficial results are representative of the RAL test environment only and intended for research & comparison purposes.

<b>Total Absorption</b>	Absorption
(Sabins)	Coefficient
4.5.04	0.04
	0.21
	0.06
	0.02
	0.15
7.29	0.10
16.02	0.22
25.43	0.35
35.48	0.49
46.87	0.65
56.45	0.78
71.51	0.99
78.54	1.09
87.71	1.22
91.16	1.27
90.60	1.26
91.76	1.27
91.32	1.27
89.13	1.24
87.58	1.22
82.63	1.15
80.23	1.11
82.48	1.15
83.55	1.16
83.93	1.17
84.41	1.17
87.25	1.21
81.23	1.13
	(Sabins)  15.31 4.43 1.40 11.07 7.29  16.02 25.43 35.48 46.87 56.45 71.51 78.54 87.71 91.16 90.60 91.76 91.32 89.13 87.58 82.63 80.23 82.48 83.55 83.93 84.41 87.25



® RIVERBANK ACOUSTICAL LABORATORIES IS ACCREDITED BY NVLAP (LAB CODE 100227-0) FOR ACOUSTICAL TESTING SERVICES IN ACCORDANCE WITH ISO/IEC 17025:2017 AND FOR THIS PROCEDURE. THIS REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY RAL, NVLAP, NIST, OR ANY AGENCY OF THE U.S. GOVERNMENT.

THIS REPORT SHALL NOT BE MODIFIED WITHOUT THE WRITTEN APPROVAL OF RAL. THE RESULTS REPORTED APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR TESTING; RAL ASSUMES NO RESPONSIBILITY FOR THE PERFORMANCE OF ANY OTHER SAMPLE.

1512 S BATAVIA AVENUE GENEVA, IL 60134 630-232-0104

Test Report

www.riverbankacoustics.com

FOUNDED 1918 BY WALLACE CLEMENT SABINE

Archifibe Inc. 2022-09-28

RALTM-A22-428

Page 9 of 9

#### **APPENDIX B: Instruments of Traceability**

Specimen: EzoLayer 50mm (See Full Report)

<b>Description</b>	<b>Model</b>	Serial <u>Number</u>	Date of Certification	Calibration <u>Due</u>
System 1	Type 3160-A-042	3 <del>160-</del> 106968	2022-07-12	2023-07-12
Bruel & Kjaer Mic And Preamp C	Type 4943-B-001	2311439	2022-05-02	2023-05-02
Bruel & Kjaer Pistonphone	Type 4228	2781248	2022-07-22	2023-07-22
EXTECH Hygro 959	SD700	A099959	2022-03-22	2023-03-22

#### **APPENDIX C: Revisions to Original Test Report**

Specimen: EzoLayer 50mm (See Full Report)

Revision **Date** 

2022-10-06 Original report issued

**END** 

